Ceramic Urinals with Radar Flushing Unit SLP 12R, SLP 37R







SLP 12 - VILA WITHOUT A COVER

SLP 37 - VILA WITH A COVER


Characteristics





- includes Bluetooth control (Sanela Control app available for download)
- economy flushing by 1 liter of water
- system Soft-close (SLP 37R)
- easy installation
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- monitoring of battery capacity (for models with index B)
- water flow could be regulated by ball valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 waste outlet Ø 50 mm
- 2 holes for fitting
- 3 water supply
- 4 power supply 230 V AC (SLP 12/37RZ)
- 5 power supply 24 V DC (SLP 12/37R)
- 6 inlet fitting
- 7 mounting box

Technical Specification

Mounting box dimension Operating voltage

- SLP 12R, 37R
- SLP 12RZ, 37RZ
- SLP 12RB, 37RB

Power input

- operating by 24 V DC
- operating by 6 V

Recommended flow pressure

Rate of flow

Water inlet

Water outlet

140 x 140 x 75 mm

24 V DC

230 V AC/50 Hz

6 V

8 W


3 W

0,1 - 0,6 MPa 18 l/min (inf.data)

male thread G 3/4" inlet fitting with a rubber

sealing

SLA 11C



^{*} for the height of the front edge of the urinal 650 mm above floor



SLA 11B

Supply Specification

SLP 37RB

SLP 12R - Supply No. 01124
SLP 12RZ - Supply No. 01125
SLP 12RB - Supply No. 11127
SLP 37R - Supply No. 01374
SLP 37RZ - Supply No. 01375

Supply No. 11377

ceramic urinal with the radar flushing unit including Bluetooth module, plastic mounting box with brass screw coupling, electromagnetic valve and ball valve, inlet fitting with a rubber sealing, siphon, mounting set, plastic cover (SLP 37xx), power supply (for models with index RZ), 4 psc. AA alkaline batteries

1,5 V, 2700 mAh with battery case (for models with index RB)

Radar Urinal Flushing Units

Radar Urinal Flushing Units

Recommended Accessories

SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of flushing units
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of flushing units
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units
SLZ 04X	-	Supply No. 10049	power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units
SLZ 06	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of flushing unit
SLD 04	-	Supply No. 07040	remote control for an adjustment of parameters
SLA 11	-	Supply No. 06110	deodorising urinal screen - orange, mango scent
SLA 11A	-	Supply No. 06111	deodorising urinal screen - red, kiwi and grapefruit scent
SLA 11B	-	Supply No. 06112	deodorising urinal screen - transparent, honeysuckle scent
SLA 11C	-	Supply No. 06113	deodorising urinal screen - blue, cotton bloom scent
SLR 01	-	Supply No. 08010	mounting frame to the plasterboard for urinal and flushing unit with mounting
			box behind urinal
SLR 22	-	Supply No. 08220	mounting frame for plasterboard constructions, for mounting to the floor and to the back wall, is destined for ceramic urinals and Sanela stainless steel urinals (SLPN 07, SLPN 09) and infra-red flushing unit, which is placed above the urinal (SLP 02, SLP 06)
SLA 36 SANELA C	- ОN1	Supply No. 06360 ROL APP	set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B) available for download on the App Store and Play Store