




Characteristics

- economical aerator, rate of flow 6 l/min
- hygienic flush
- are destined for cold and hot water, temperature is regulated by mixer
- water is flowing as long as hands are in the active range
- water stops flowing after removal of hands from the active range of sensor after adjustable time delay (can be set in range 0,25 - 7,75 s)
- function of automatic water stop after 5 minut of continuous flow
- monitoring of battery capacity (for models with index B)
- START/STOP program
- parameter adjustment using by the remote control SLD 03

Technical Specification

| Dimension of the mounting box | 90 x 80 x 40 mm | |
|--|----------------------|--|
| Operating voltage | | |
| SLU 42K | 24 V DC | |
| SLU 42KB | 6 V | |
| Power input | | |
| operating by 24 V DC | 3 W | |
| operating by 6 V | 2 W | |
| Battery life | | |
| 4 pcs. AA alkaline batteries | approx. 2 years | |
| AA, 1,5 V, 2700 mAh | (100 uses per day) | |
| Active range | | |
| standard | 0,11 - 0,15 m | |
| START/STOP program | 0,05 - 0,15 m | |
| Recommended flow pressure | 0,1 - 0,6 MPa | |
| Rate of flow | 6 l/min. (inf. data) | |
| Water inlet | male thread G 1/2" | |
| water miet | male thread G 1/2 | |

Installation Drawing



- 2 inlet of cold water
- 3 faucet with electronics
- 4 active range
- 5 feed cable from the power supply

Supply Specification

SLU 42K - Supply No. 03420 faucet with mixer, electronics and solenoid valve, plastic mounting box, SLU 42KB - Supply No. 03425 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh (SLU 42KB)

Recommended Accessories

| SLZ 01Y SLZ 01Z SLZ 04Y SLZ 04Z SLZ 04X SLD 03 SLA 36 SLA 56A SLA 56B | Supply No. 05012 Supply No. 05011 Supply No. 05042 Supply No. 05041 Supply No. 10049 Supply No. 07030 Supply No. 06360 Supply No. 06560 Supply No. 06561 | power supply 24 V DC for operating of max. 10 pcs. of washbasin taps power supply 24 V DC for operating of max. 20 pcs. of washbasin taps power supply 24 V DC for DIN rail, for operating of max. 10 pcs. of washbasin taps power supply 24 V DC for DIN rail, for operating of max. 20 pcs. of washbasin taps power supply 24 V DC for DIN rail, for operating of max. 30 pcs. of washbasin taps power supply 24 V DC for DIN rail, for operating of max. 30 pcs. of washbasin taps remote control for an adjustment of parameters set of 4 pcs. alkaline batteries AA, 1,5 V, 2700 mAh (for models with index B) economical aerator 3,8 l/min economical aerator 1,9 l/min |
|---|--|--|
|---|--|--|