Ceramic Urinal with the Radar Flushing Unit SLP 27R






SLP 27 - Roca - Chic

Characteristics



- economy flushing by 1 liter of water
- easy installation by the help of paper drill template
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameters adjustment by remote control SLD 04 without the necessity to dismantle the urinal from the wall (acoustic setting indication)
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 water outlet Ø 50 mm
- 2 holes for fitting
- 3 water supply
- 4 power supply 24 V DC or 230 V AC
- 5 holes for wall plug

Technical Specification

Operating voltage

■ SLP 27R

SLP 27RZ

Power input

operating by 24 V DC

Recommended flow pressure

Rate of flow Water inlet

Water outlet

24 V DC

230 V AC/50 Hz

8 W

0,1 - 0,6 MPa 18 I/min (inf. data) male thread G 1/2"

inlet fitting with a rubber

sealing



SLA 41



SLA 11



SLA 11A





SLA 11B **SLA 11C**

Dimensions (mm)	Α	В	С	D	Е	F	G	I
SLP 27 - CHIC	475	225	240	35	70	360	80	10

^{*} for the height of the front edge of the urinal 650 mm above the floor

Supply Specification

Supply No. 01274 SLP 27R -

ceramic urinal with the radar flushing unit on the mounting rail.

SLP 27RZ -**Supply No. 01275** electromagnetic valve, connecting hoses, angle valve with filter and check valve, inlet fitting with a rubber seal, siphon, paper drill template, power supply (SLP 27RZ)

Recommended Accessories

SLZ 01Y **Supply No. 05012** power supply 24 V DC for operating of max. 5 pcs. of flushing units **SLZ 01Z** Supply No. 05011 power supply 24 V DC for operating of max. 9 pcs. of flushing units **SLZ 04Y Supply No. 05042** power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units SLZ 04Z **Supply No. 05041** SLZ 04X -**Supply No. 10049** power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units **SLZ 06 Supply No. 05060** power supply 24 V DC for operating of max. 1 pc. of flushing unit **SLD 04 Supply No. 07040** remote control for an adjustment of parameters **SLA 11 Supply No. 06110** deodorising urinal screen - orange colour, mango scent deodorising urinal screen - red colour, kiwi and grapefruit scent SLA 11A -**Supply No. 06111 Supply No. 06112** SLA 11B deodorising urinal screen - transparent colour, honeysuckle scent

SLA 11C -**Supply No. 06113** deodorising urinal screen - blue colour, cotton bloom scent SI A 41 **Supply No. 06410** stainless steel sieve for urinal CHIC

Supply No. 08015 mounting frame to the plasterboard for the urinal with radar flushing unit SLR 01L on the mounting rail