

# Automatic Wall-mounted Steel Stainless Washbasin Tap SLU 14




## Characteristics



- **hygienic flush**
- is destined for cold or premixed water
- index X - brushed finish
- water is flowing as long as hands are in the active range
- water stops flowing after removal of hands from the active range of sensor after adjustable time delay (can be set in range 0,25 – 7,75 s)
- function of automatic water stop after 5 minut of continuous flow
- monitoring of battery capacity (for models with index B)
- START/STOP program
- parameter adjustment using by the remote control SLD 03
- water flow could be regulated by ball valve

## Installation Drawing



- 1 - water supply  
2 - spout 125 mm  
3 - active range  
4 - mounting box  
5 - cover with electronics

## Technical Specification

<b>Stainless steel cover dimension</b>	180 x 180 x 3 mm
<b>Mounting box dimension</b>	164 x 154 x 75 mm
<b>Operating voltage</b>	
▪ SLU 14, 14X	24 V DC
▪ SLU 14B, 14BX	6 V
<b>Power input</b>	
▪ operating by 24 V DC	7 W
▪ operating by 6 V	3 W
<b>Battery life</b>	
▪ 4 pcs. AA alkaline batteries AA, 1,5 V, 2700 mAh	approx. 2 years (100 uses per day)
<b>Active range</b>	
▪ standard	0,27 - 0,35 m
▪ START/STOP program	0,05 - 0,15 m
<b>Recommended flow pressure</b>	0,1 - 0,6 MPa
<b>Rate of flow</b>	12 l/min. (inf. data)
<b>Water inlet</b>	male thread G 3/4"

## Supply Specification

SLU 14	- Supply No. 03140	stainless steel cover with spout and electronics, stainless steel mounting box
SLU 14B	- Supply No. 03145	with brass screw coupling, electromagnetic valve and ball valve, 4 pcs. AA alkaline
SLU 14X	- Supply No. 64144	batteries 1,5 V, 2700 mAh (for models with index B)
SLU 14BX	- Supply No. 64145	

## Recommended Accessories

SLZ 01Y	- Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of washbasin taps
SLZ 01Z	- Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of washbasin taps
SLZ 04Y	- Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of washbasin taps
SLZ 04Z	- Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of washbasin taps
SLZ 04X	- Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of washbasin taps
SLZ 06	- Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of washbasin tap
SLD 03	- Supply No. 07030	remote control for an adjustment of parameters
SLT 04	- Supply No. 09040	thermostatic valve 3/4", rate of flow 28 l/min by the pressure 0,1 MPa
SLT 05	- Supply No. 09050	thermostatic valve 1/2", rate of flow 42 l/min by the pressure 0,1 MPa
SLA 36	- Supply No. 06360	set of 4 pcs. alkaline batteries AA, 1,5 V, 2700 mAh (for models with index B)