

# Coin and Token Machines for Door Opening

## SLZA 40, SLZA 40V



SLZA 40



SLZA 40V



SLZA 40Z




SLZA 40VZ

### Characteristics




- for disabled and persons with limited mobility
- vandal-proof
- coin and token machine for door opening (12 V DC a 24 V DC), electromagnetic lock
- after inserting the minimal requested credit (coin or token) the door lock opens for adjusted time
- the machine adds up the coins but does not return
- model with index V - with eurokey
- model with index Z - recessed
- parameters adjustment on display inside of the machine using by the remote control SLD 05 (door lock unlocking interval, value for unlocking, current euro exchange rate, choice of control - mode **with** or **without** door contact)
- lockable
- for indoor use, temperature range +5 to +40 °C
- material AISI - 304
- could be made to order from stainless steel AISI - 316L
- brushed finish




### Installation Drawing





SLZA 40



SLZA 40V



SLZA 40Z



SLZA 40VZ

### Technical Specification

Niche dimensions (index Z)  
Operating voltage  
Total power consumption (including 12 V DC door lock)  
Total power consumption (including 24 V DC door lock)  
Accepted coins

265 x 127 x 125 mm  
24 V DC

12 W

10 W

1 and 2 €, token (other currencies on request)

Adjustable time for unlocking

1 - 310 s, standard 10 s

Adjustable minimum value for unlocking

1 - 19 €, standard 1 €

## Supply Specification

SLZA 40	-	Supply No. 88400	stainless steel coin machine with electronics, coin holder and coin box, eurokey,
SLZA 40V	-	Supply No. 88404	set of keys (2 pcs.) mounting frame (for models with index Z), remote control SLD 05
SLZA 40Z	-	Supply No. 88401	
SLZA 40VZ	-	Supply No. 88405	

## Recommended Accessories

SLZA 50	-	Supply No. 88500	set of 50 pcs. of tokens for coin machine
SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 1 pc. of machine
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 3 pcs. of machines
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 1 pc. of machine
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 3 pcs. of machines
SLZ 04X	-	Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of machines