Coin and Token Machines for Door Opening with GSM Module SLZA 40G, SLZA 40GV









SLZA 40GV







SLZA 40GVZ

Characteristics







- for disabled and persons with limited mobility
- vandal-proof
- coin and token machine for door opening (12 V), electromagnetic lock, GSM module
- after inserting the minimal requested credit (coin or token) the door lock opens for adjusted time
- SMS message about filling in the cash register, including the current value of CZK
- the machine adds up the coins but does not return
- model with index V with eurokey
- model with index Z recessed
- parameters adjustment on display inside of the machine using by the remote control SLD 05 (door lock unlocking interval, value for unlocking, current euro exchange rate, choice of control - mode with or without door contact)
- lockable
- for indoor use, temperature range +5 to +40 °C
- material AISI 304
- could be made to order from stainless steel AISI 316L
- brushed finish


Installation Drawing

SLZA 40G









SLZA 40GVZ SLZA 40GZ

Technical Specification

Niche dimensions (index Z) Operating voltage Max. power input of electromagnetic lock Power input in sleep mode **Accepted coins**

Adjustable time for unlocking

Adjustable minimum value for unlocking

265 x 127 x 125 mm 24 V DC

2.5 W 1 and 2 €, token (other currencies on request) 1 - 310 s, standard 10 s

20 W

1 -19 €. standard 1 € SLZA 40G - Supply No. 88402 SLZA 40GV - Supply No. 88406

stainless steel coin machine with electronics, coin holder and coin box, eurokey, set of keys (2 pcs.), mounting frame (for models with index Z), remote control SLD 05

SLZA 40GZ - Supply No. 88403

SLZA 40GVZ - Supply No. 88407

Recommended Accessories

SLZA 50 - Supply No. 88500 set of 50 pcs. of tokens for coin machine

SLZ 01Y - Supply No. 05012 power supply 24 V DC for operating of max. 1 pc. of machine power supply 24 V DC for operating of max. 3 pcs. of machines

SLZ 04Y - Supply No. 05042 power supply 24 V DC for DIN rail, for operating of max. 1 pc. of machine power supply 24 V DC for DIN rail, for operating of max. 3 pcs. of machines SLZ 04X - Supply No. 10049 power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of machines