Coin and Token Devices for Door Opening SLZA 40, SLZA 40V







SLZA 40

SLZA 40V





SLZA 40Z

SLZA 40VZ


Characteristics







- for disabled and persons with limited mobility
- vandal-proof
- coin and token device for door opening (12 V DC and 24 V DC), electromagnetic lock
- after inserting the minimal requested credit (coin or token) the door lock opens for adjusted time
- the device adds up the coins but does not return
- model with index V with eurokey
- model with index Z recessed
- parameters adjustment on display inside of the device using by the remote control SLD 05 (door lock unlocking interval, value for unlocking, current euro exchange rate, choice of control - mode with or without door contact)
- lockable
- for indoor use, temperature range +5 to +40 °C
- material stainless steel AISI 304 (1.4301)
- brushed finish

Installation Drawing









SLZA 40

SLZA 40Z

SLZA 40V











SLZA 40VZ

Technical Specification

Niche dimensions (index Z) **Dimensions**

•	SL	ZΑ	40
	SI	7Δ	40V

- SLZA 40Z
- SLZA 40VZ

Weight

- SLZA 40 SLZA 40V
- SLZA 40Z
- SLZA 40VZ Thickness of material

Operating voltage **Total power consumption** (including 12 V DC door lock) **Total power consumption** (including 24 V DC door lock)

Accepted coins

Adjustable time for unlocking

Adjustable minimum value for unlocking

265 x 127 x 125 mm

230 x 139 x 120 mm 277 x 139 x 120 mm 285 x 145 x 142 mm 285 x 145 x 142 mm

2,9 kg 4,6 kg 3,2 kg 4,8 kg 1,5 mm 24 V DC

12 W

10 W 1 and 2 €. token (other currencies on request) 1 - 310 sec., standard 10 sec.

1 -19 €. standard 1 €

Supply Specification

SLZA 40 - Supply No. 88400 stainless steel coin device with electronics, coin holder and coin box, eurokey,

SLZA 40V - Supply No. 88404 set of keys (2 pcs.) mounting frame (for models with index Z), remote control SLD 05

SLZA 40Z - Supply No. 88401 SLZA 40VZ - Supply No. 88405

Recommended Accessories

SLZ 01Y - Supply No. 05012 power supply 24 V DC for operating of max. 1 pc. of device SLZ 01Z - Supply No. 05011 power supply 24 V DC for operating of max. 3 pcs. of devices

SLZ 04Y - Supply No. 05042 power supply 24 V DC for DIN rail, for operating of max. 1 pc. of device
SLZ 04Z - Supply No. 05041 power supply 24 V DC for DIN rail, for operating of max. 3 pcs. of devices
SLZ 04X - Supply No. 10049 power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of devices

SLZA 50 - Supply No. 88500 set of 50 pcs. of tokens for coin device