Radar Flushing Unit for Urinal MERINO (Roca-Inker) **SLP 35S**






Characteristics



- radar flushing unit for urinal MERINO (Roca-Inker)
- economy flushing by 1 liter of water
- easy installation by the help of paper drill template
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameters adjustment by remote control SLD 04 without the necessity to dismantle the urinal from the wall (acoustic setting indication)
- automatic flushing after each 6 hours non-use
- monitoring of battery capacity (for models with index B)
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 water outlet Ø 50 mm
- 2 holes for fitting
- 3 water supply
- 4 power supply 24 V DC or 230 V AC
- 5 holes for wall plug

Ε

70

F

340

G

Н

215

Technical Specification

Operating voltage

24 V DC SLP 35S 230 V AC/50 Hz ■ SLP 35Z ■ SLP 35B 6 V

Power input

operating by 24 V DC 8 W operating by 6 V

Recommended flow pressure

Rate of flow Water inlet Water outlet 3 W 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing

Illustrative photo:







SLA 11

SLA 11A





SLA 11B

SLA 11C

Supply	Speci	ificat	ion

Dimensions (mm)

SLP 35 - INKER

SLP 35B

SLP 35S Supply No. 11351 **SLP 35Z Supply No. 01351**

radar flushing unit on the mounting rail, electromagnetic valve, connecting hoses, angle valve with filter and check valve, inlet fitting with a rubber sealing, siphon, **Supply No. 11356** drill template, power supply (SLP 35Z), 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLP 35B)

Recommended Accessories

В

280

405

С

290

* for the height of the front edge of the urinal 650 mm above the floor

D

140

SLZ 01Y power supply 24 V DC for operating of max. 5 pcs. of flushing units **Supply No. 05012 SLZ 01Z** Supply No. 05011 power supply 24 V DC for operating of max. 9 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units **SLZ 04Y** Supply No. 05042 **SLZ 04Z** Supply No. 05041 power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units

SLZ 04X **Supply No. 10049** power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units

SLZ 06 Supply No. 05060 power supply 24 V DC for operating of max. 1 pc. of flushing unit

SLD 04 Supply No. 07040 remote control for an adjustment of parameters

SLA 11 Supply No. 06110 deodorising urinal screen - orange colour, mango scent

SLA 11A Supply No. 06111 deodorising urinal screen - red colour, kiwi and grapefruit scent SLA 11B Supply No. 06112 deodorising urinal screen - transparent colour, honeysuckle scent

SLA 11C Supply No. 06113 deodorising urinal screen - blue colour, cotton bloom scent

SLR 09 Supply No. 08090 mounting frame for ceramic urinals with built-in flush or for stainless steel washbasins **SLA 36** set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B) **Supply No. 06360**