# Ceramic Urinal with the Radar Flushing Unit SLP 23S






SLP 23 - CAPRINO

### Characteristics

- includes Bluetooth control
   (Sanela Control app available for download)
- economy flushing by 1 liter of water
- easy installation
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal,when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- monitoring of battery capacity (for models with index B)
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 water outlet Ø 50 mm
- 2 holes for fitting
- 3 water supply
- 4 power supply 24 V DC or 230 V AC
- 5 holes for wall plugs

D

45

Ε

50

F

125

G

70

К

235

6 - power supply

SLP 23

С

240

## **Technical Specification**

#### Operating voltage

SLP 23S
SLP 23Z
SLP 23B
Power input
operating by 24 V DC
operating by 6 V
Recommended flow pressure
Rate of flow
Water inlet
Water outlet

L

60

24 V DC 230 V AC/50 Hz 6 V

8 W 3 W 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing



## **Supply Specification**

**Dimensions** (mm)

**SLP 23 - CAPRINO** 

SLP 23S	-	Supply No. 01233	с
SLP 23Z	-	Supply No. 01234	۷
SLP 23B	-	Supply No. 01232	W

Α

400

В

260

\* for the height of the front edge of the urinal 650 mm above floor

ceramic urinal with radar flushing unit including Bluetooth module, electromagnetic valve, connecting hoses, angle valve with a filter and check valve, inlet fitting with a rubber sealing, siphon, mounting set, power supply (SLP 23Z), 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLP 23B)

**Radar Urinal Flushing Units** 

## **Recommended Accessories**

SLZ 01Y-Supply No. 05012power supply 24 V DC for operating of max. 5 pcs. of flushing unitsSLZ 01Z-Supply No. 05011power supply 24 V DC for operating of max. 9 pcs. of flushing unitsSLZ 04Y-Supply No. 05041power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing unitsSLZ 04Z-Supply No. 05041power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing unitsSLZ 04X-Supply No. 10049power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing unitsSLZ 06-Supply No.05060power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing unitsSLD 04-Supply No.07040remote control for an adjustment of parametersSLA 11-Supply No. 06110deodorising urinal screen - orange, mango scentSLA 11A-Supply No. 06111deodorising urinal screen - red, kiwi and grapefruit scentSLA 11C-Supply No. 06113deodorising urinal screen - blue, cotton bloom scentSLR 09-Supply No. 06360set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B)SANELA CONTROL APPavailable for download on the App Store and Play Store
--