




SLP 49 - CAPRINO PLUS RIMLESS

Characteristics

- includes Bluetooth control (Sanela Control app available for download)
- economy flushing by 1 liter of water
- easy installation by the help of paper drill template
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- monitoring of battery capacity (for models with index B)
- possibility to regulate a water flow by the ball valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 water outlet Ø 50 mm
- 4 power supply 24 V DC

Technical Specification

Operating voltage

 SLP 49B SLP 49S SLP 49Z Power input operating by 24 V DC operating by 6 V **Recommended flow pressure** Rate of flow Water inlet Water outlet

6 V 24 V DC 230 V AC/50 Hz

8 W 3 W 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing

| Dimensions (mm) | A | В | С | D | E | F | G |
|-------------------------------|-----|-----|-----|----|----|-----|----|
| SLP 49 - CAPRINO PLUS RIMLESS | 400 | 260 | 240 | 50 | 60 | 160 | 60 |

* for the height of the front edge of the urinal 650 mm above the floor



SLA 26

Supply Specification

| SLP 49S | - | Supply No. 01498 |
|---------|---|------------------|
| SLP 49Z | - | Supply No. 01499 |
| SLP 49B | - | Supply No. 01492 |

ceramic urinal with radar flush including Bluetooth module, electromagnetic valve, connecting hoses, angle valve with filter and check valve, inlet fitting with a rubber sealing, siphon, mounting set, paper drill template, power supply (SLP 49Z), 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLP 49B)

Recommended Accessories

| SLZ 01Y SLZ 01Z SLZ 04Y SLZ 04Z SLZ 04X SLZ 06 SLD 04 SLA 11 SLA 11A SLA 11A SLA 11B SLA 11C SLA 26 SLR 09 SLA 36 SANELA C | | Supply No. 10049 Supply No. 05060 Supply No. 07040 Supply No. 06110 Supply No. 06111 Supply No. 06112 Supply No. 06113 Supply No. 06260 Supply No. 08090 Supply No. 06360 | power supply 24 V DC for operating of max. 5 pcs. of flushing units power supply 24 V DC for operating of max. 9 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units power supply 24 V DC for operating of max. 1 pc. of flushing unit remote control for an adjustment of parameters deodorising urinal screen - orange colour, mango scent deodorising urinal screen - red colour, kiwi and grapefruit scent deodorising urinal screen - transparent colour, honeysuckle scent deodorising urinal screen - blue colour, cotton bloom scent stainless steel sieve for urinals Golem and Caprino plus rimless mounting frame for ceramic urinals with built-in flush or for ceramic washbasins set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B) available for download on the App Store and Play Store |
|---|--|--|---|
|---|--|--|---|