Coin and Token Shower Timers for One Shower SLZA 03M, SLZA 03MZ







SLZA 03M

SLZA 03MZ

Characteristics





- hygienic flush
- vandal-proof
- direct control
- after inserting a coin or a token the device starts water flow on several seconds in the shower
- 30 s before the end of water supply the user is warned by interrupting of water flow
- the device adds up the coins but does not return
- index Z recessed
- parameters adjustment using by the remote control SLD 05 (adjustment of shower time according to the thrown coin or token, time delay of switch on, possible activation of hygienic flush, current euro exchange, token value)
- lockable
- for indoor use, temperature range +5 to +40 °C
- material stainless steel AISI 304 (1.4301)
- brushed finish

Installation Drawing

120 145 125

SLZA 03M

SLZA 03MZ

Technical Specification

Niche dimensions (index Z)	265 x 127 x 125 mm
Dimensions	

SLZA 03M

SLZA 03MZWeight

Weight ■ SLZA 03M

 SLZA 03MZ
 Thickness of material Operating voltage

Power input

Accepted coins

Switch on delay

Showering time

on request)
0 - 300 sec.,
standard
30 sec.

4,5 kg

6,2 kg

1,5 mm 24 V DC

10 W (2,5 W

in sleep mode)

1 and 2 €, token (other currencies

230 x 139 x 120 mm

285 x 145 x 142 mm

5 - 1200 sec.

Supply Specification

SLZA 03M - Supply No. 88031 st

stainless steel coin device with electronics, coin holder and coin box,

set of keys (2 pcs.)

SLZA 03MZ - Supply No. 88032

stainless steel coin device with electronics, coin holder and coin box,

set of keys (2 pcs.), mounting frame

Required Accessories



SLZA 20 88200

Shower control without piezo button - premixed water

Coin and Token Shower Timers






SLZA 20H 88205	Shower control without piezo button - for cold and hot water, temperature regulated by mixer
----------------	--



SLZA 20T 88206	Shower control without piezo button - for cold and hot water, temperature regulated by thermostatic mixer
----------------	---

⁻ thermostatic valve nut spanner SLA 64



SLZA 21 88210	Stainless steel shower panel without piezo button - premixed water
---------------	--



	wer panel without piezo ot water, temperature
--	--



SLZA 21T	88216	Stainless steel shower panel without piezo button - for cold and hot water, temperature
		regulated by thermostatic mixer

Recommended Accessories

SLZ 01Y SLZ 01Z		Supply No. 05012 Supply No. 05011	power supply 24 V DC for operating of max. 1 pc. of shower power supply 24 V DC for operating of max. 3 pcs. of showers
SLZ 04Y		Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 1 pc. of shower
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 3 pcs. of showers
SLZ 04X	-	Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers
SLD 05	-	Supply No. 07050	remote control for an adjustment of parameters
SLA 64	-	Supply No. 06640	thermostatic valve nut spanner (SLZA 20T)
SLZA 50	-	Supply No. 88500	set of 50 pcs. of tokens for coin device