Coin and Token Shower Timers for Four to Eight Showers SLZA 02N, SLZA 02NZ





SLZA 02N



SLZA 02NZ


Characteristics







- hygienic flush
- vandal-proof
- choice of shower by the machine
- after inserting a coin or a token the device assigns the shower to the user and shows the number of shower on display
- interactive control
- after inserting a coin or a token the device starts water flow on several seconds to indicate the chosen shower
- the user can start or stop the water flow directly in the shower
- 30 s before the end of water supply the user is warned by interrupting of water flow
- the device adds up the coins but does not return
- index Z recessed
- parameters adjustment using by the remote control SLD 05 (adjustment of shower time according to the thrown coin or token, time delay of switch on, possible activation of hygienic flush, current euro exchange, token value, display contrast, possibility switch off some from showers)
- marking of the buttons by symbols could be made to order
- the possibility of obtaining the statistical information, device diagnostics
- lockable
- for indoor use, temperature range +5 to +40 °C
- material stainless steel AISI 304 (1.4301)
- brushed finish


Installation Drawing





SLZA 02N





SLZA 02NZ

Technical Specification

Niche dimensions (index Z)

Dimensions

SLZA 02N SLZA 02NZ

Weight

SLZA 02NSLZA 02NZ

Thickness of material Operating voltage

Power input Accepted coins

Accepted coins
Switch on delay

Showering time

335 x 200 x 125 mm

300 x 165 x 132 mm 360 x 225 x 132 mm

4,5 kg 6,2 kg

6,2 kg 1,5 mm 24 V DC

91 W (depends on the accessories and the number of showers)

1 and 2 €, token (other currencies on request)

0 - 255 sec., standard 30 sec.

5 - 1200 sec.

set of keys (2 pcs.)

SLZA 02NZ - Supply No. 88024

stainless steel coin device with electronics, coin holder and coin box,

set of keys (2 pcs.), mountig frame

Required Accessories



| SLZA 15 | 88150 | Valves distributor on DIN rail |
|---------|-------|--------------------------------------|
| SLZA 17 | 88170 | Push buttons distributor on DIN rail |




| SLZA 20P | 88207 | Shower control with piezo button - premixed water |
|----------|-------|---|
| | | - premixed water |





| Shower control with piezo button - for cold and hot water, temperature regulated by thermostatic mixer |
|--|
|--|

- thermostatic valve nut spanner SLA 64



| SLZA 21P Stainless steel shower panel with piezo button - premixed water | |
|--|--|
|--|--|



| SLZA 21PH | 88218 | Stainless steel shower panel with piezo button - for cold and hot water, temperature regulated by mixer |
|-----------|-------|---|
|-----------|-------|---|





SLZA 21PT

88219

Stainless steel shower panel with piezo button - for cold and hot water, temperature regulated by thermostatic mixer

Recommended Accessories

| SLZ 01Y SLZ 01Z SLZ 04Y SLZ 04Z SLZ 04X SLD 05 SLA 03 SLA 39 SLA 40 SLA 64 | | Supply No. 05012 Supply No. 05011 Supply No. 05042 Supply No. 05041 Supply No. 10049 Supply No. 07050 Supply No. 06030 Supply No. 06390 Supply No. 06400 Supply No. 06640 | power supply 24 V DC for operating of max. 5 pcs. of showers power supply 24 V DC for operating of max. 9 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers remote control for an adjustment of parameters vandal-proof shower head vandal-proof shower head vandal-proof shower head with possibility to set an angle of water flow thermostatic valve nut spanner (SLZA 20PT) |
|---|---|--|---|
| SLA 64 SLZA 50 | | | · |
| SLZA 50 | - | Supply No. 88500 | set of 50 pcs. of tokens for coin machine |