



Characteristics





- hygienic flush
- vandal-proof
- wall hung shower panel with piezo button for automatic device with index N
- is designed for cold and hot water, temperature is regulated by thermostatic mixer
- safety fuse against scalding
- stop flowing of hot water in case of cold water failure

SLZA 21PT

Installation Drawing

Technical Specification

Dimensions Recommended flow pressure Rate of flow Water inlet 1050 x 220 x 143 mm 0,1 - 0,6 MPa 9 l/min. (inf. data) male thread G 1/2"

- 1 water supply
- 2 power supply from the device
- 3 shower head
- 4 piezo button
- 5 thermostatic mixer

Supply Specification

SLZA 21PT - **Supply No. 88209** stainless steel shower panel, electromagnetic valve (1 pc.), thermostatic mixer, connecting hoses, angle valve with filter and check valve (2 pcs.)

Designed for Products

SLZA 01N	- Supply No. 88013	coin and token automatic device for one to three showers
SLZA 01NZ	- Supply No. 88014	coin and token automatic device for one to three showers
-		
SLZA 01LN	- Supply No. 88017	coin and token automatic device for one to three showers
SLZA 01LNZ	- Supply No. 88018	coin and token automatic device for one to three showers
SLZA 02N	- Supply No. 88023	coin and token automatic device for four to twelve showers
SLZA 02NZ	- Supply No. 88024	coin and token automatic device for four to twelve showers
SLZA 02LN	- Supply No. 88029	coin and token automatic device for four to eight showers
SLZA 02LNZ	- Supply No. 88020	coin and token automatic device for four to eight showers
SLZA 03N	- Supply No. 88033	coin and token automatic device for one shower
SLZA 03NZ	- Supply No. 88034	coin and token automatic device for one shower