





**SLP 99B** 


**Characteristics** 





- DESIGNED FOR URINAL FLOW (Keramag) No. 235900
- includes Bluetooth control
  - (Sanela Control app available for download)
- THE URINAL DOES NOT HAVE TO BE SENT FOR ASSEMBLY (THE RADAR SENSOR IS SUPPLIED SEPARATELY)
- SLP 99S 24 V DC, pre-wall mounting (water supply with flexi
- SLP 99Z 230 V AC, including power supply unit
- SLP 99B 6 V, including housing with 4 pc AA batteries
- economy flushing by 1 liter of water
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

## **Installation Drawing**



- 1 water outlet Ø 50 mm
- 2 2 x holes for fitting
- 3 water supply G 1/2"
- 4 power supply 24 V DC (SLP 99S) or 230 V AC (SLP 99Z)
- 5 2 x holes for wall plug Ø 8 mm

Dimensions (mm)	Α	В	С	D	Е	F	G	Н
SLP 99 - FLOW	375	245	220	110	83	315	65	208

<sup>\*</sup> for the height of the front edge of the urinal 650 mm above the floor

# **Technical Specification**

### Operating voltage

■ SLP 99S

■ SLP 99Z

■ SLP 99B

### **Power input**

• operating by 24 V DC

operating by 6 V

Recommended flow pressure

Rate of flow

Water inlet Water outlet

### 24 V DC

230 V AC/50 Hz

6 V

8 W

3 W

0,1 - 0,6 MPa 12 l/min (inf. data) male thread G 1/2"

inlet fitting with a rubber

sealing









SLA 11A





**SLA 11C** 

Radar Urinal Flushing Units

# Radar Urinal Flushing Units

# **Supply Specification**

SLP 99S - Supply No. 21992 radar flushing unit including Bluetooth module on the mounting rail, electromagnetic valve, connecting hoses, angle valve, inlet fitting with a rubber sealing, siphon,power supply
SLP 99B - Supply No. 21996 (SLP 99Z), 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLP 99B)

# **Recommended Accessories**

SLZ 01Y	-	<b>Supply No. 05012</b>	power supply 24 V DC for operating of max. 5 pcs. of flushing units				
<b>SLZ 01Z</b>	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of flushing units				
SLZ 04Y	-	<b>Supply No. 05042</b>	power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units				
<b>SLZ 04Z</b>	-	<b>Supply No. 05041</b>	power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units				
SLZ 04X	-	Supply No. 10049	power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units				
<b>SLZ 06</b>	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of flushing unit				
SLD 04	-	Supply No. 07040	remote control for an adjustment of parameters				
<b>SLA 11</b>	-	Supply No. 06110	deodorising urinal screen - orange colour, mango scent				
SLA 11A	-	Supply No. 06111	deodorising urinal screen - red colour, kiwi and grapefruit scent				
SLA 11B	-	<b>Supply No. 06112</b>	deodorising urinal screen - transparent colour, honeysuckle scent				
<b>SLA 11C</b>	-	<b>Supply No. 06113</b>	deodorising urinal screen - blue colour, cotton bloom scent				
SLR 09	-	Supply No. 08090	mounting frame for ceramic urinals with built-in flush or for ceramic washbasins				
<b>SLA 36</b>	-	<b>Supply No. 06360</b>	set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B)				
SANELA CONTROL APP		TROL APP	available for download on the App Store and Play Store				