Radar Flushing Unit for Urinal APP (Flaminia) AP28G **SLP 99**






Characteristics





- DESIGNED FOR URINAL APP (Flaminia) AP28G
- includes Bluetooth control (Sanela Control app available for download)
- THE URINAL DOES NOT HAVE TO BE SENT FOR ASSEMBLY
- SLP 99S 24 V DC, the product includes a installation box with outlet fitting, it must be embedded in the wall in the space behind the urinal
- SLP 99Z 230 V AC, including power supply unit
- economy flushing by 1 liter of water
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the ball valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing



- 1 water outlet Ø 50 mm
- 2 2 x holes for fitting
- 3 water supply G 1/2"
- 4 power supply 24 V DC OI
- 5 2
- 6 inlet fitting with a rubber sealing

or 230 V AC (SLP 99Z)	
2 x hole for rail with electronics	
al as Casima militar a milata au	

7 - mounting	box with	fittings
and valve		

Dimensions (mm)	Α	В	С	D	E	F
SLP 99 - APP	530	300	220	210	5	425

* for the height of the front edge of the urinal 650 mm above the floor

Technical Specification

Operating voltage

■ SLP 99S

■ SLP 99Z **Power input**

Recommended flow pressure

Rate of flow Water inlet

Water outlet

8 W 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing

24 V DC

230 V AC/50 Hz

Illustrative photo:





SLA 11B



SLA 11A



SLA 11C

Supply Specification

Supply No. 21992 SLP 99S SLP 99Z Supply No. 21994

radar flushing unit including Bluetooth module on the mounting rail, mounting box with brass screw coupling, electromagnetic valve and ball valve, inlet fitting with a rubber sealing, power supply (SLP 99Z)

Radar Urinal Flushing Units

Recommended Accessories

SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of flushing units
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of flushing units
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units
SLZ 04X	-	Supply No. 10049	power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units
SLZ 06	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of flushing unit
SLD 04	-	Supply No. 07040	remote control for an adjustment of parameters
SLA 11	-	Supply No. 06110	deodorising urinal screen - orange colour, mango scent
SLA 11A	-	Supply No. 06111	deodorising urinal screen - red colour, kiwi and grapefruit scent
SLA 11B	-	Supply No. 06112	deodorising urinal screen - transparent colour, honeysuckle scent
SLA 11C	-	Supply No. 06113	deodorising urinal screen - blue colour, cotton bloom scent
SANFLA C	UN.	TROI APP	available for download on the App Store and Play Store