








- includes Bluetooth control (Sanela Control app available for download)
- THE URINAL DOES NOT HAVE TO BE SENT FOR ASSEMBLY (THE RADAR SENSOR IS SUPPLIED SEPARATELY)
- SLP 99S 24 V DC, pre-wall mounting (water supply with flexi hoses)
- SLP 99Z 230 V AC, including power supply unit
- easy installation by the help of paper drill template
- economy flushing by 1 liter of water
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation Drawing

SLP 99S



- 1 water outlet Ø 50 mm
- 2 holes for fitting

SLP 99Z

- 3 water supply G 1/2"
- 4 power supply
- 5 holes for wall plug
- 6 power supply (SLP 99Z)

Technical Specification

Operating voltage

■ SLP 99S

SLP 99ZPower input

Recommended flow pressure

Rate of flow Water inlet

Water outlet

24 V DC 230 V AC/50 Hz

8 W

0,1 - 0,6 MPa 18 l/min (inf. data)

male thread G 1/2"

female thread G 1/2"

Illustrative photo:





Dimensions (mm)	Α	В	С	D	Е	F	G	Н	I	J
SLP 99 - LA FONTANA 2.0	470	270	200	40	85	370	70	255	120	65

^{*} for the height of the front edge of the urinal 650 mm above the floor

Supply Specification

SLP 99S - Supply No. 21992 SLP 99Z - Supply No. 21994 radar flushing unit including Bluetooth module on the mounting rail, electromagnetic valve, connecting hoses, angle valve, siphon, mounting set, paper drill template, power supply (SLP 99Z)

Radar Urinal Flushing Units

Recommended Accessories

SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of flushing units
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of flushing units
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units
SLZ 04X	-	Supply No. 10049	power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units
SLZ 06	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of flushing unit
SLD 04	-	Supply No. 07040	remote control for an adjustment of parameters
SLA 11	-	Supply No. 06110	deodorising urinal screen - orange colour, mango scent
SLA 11A	-	Supply No. 06111	deodorising urinal screen - red colour, kiwi and grapefruit scent
SLA 11B	-	Supply No. 06112	deodorising urinal screen - transparent colour, honeysuckle scent
SLA 11C	-	Supply No. 06113	deodorising urinal screen - blue colour, cotton bloom scent
SANFLA CONTROL APP		TROL APP	available for download on the App Store and Play Store