

Safety Eyewash Showers

SLSN 22, SLSN 22D, SLSN 22V



SLSN 22

Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with two spray heads, head at an angle of 45 degrees with plastic wall holder
- wall mounted

Technical Specification

Rate of flow	14 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C

Supply Specification

SLSN 22 - Supply No. 92220 eyewash shower, plastic wall holder, flexi hose (1500 mm)



SLSN 22D

Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with two spray heads, head at an angle of 45 degrees with desk holder
- mounting on the desk

Technical Specification

Rate of flow	14 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C

Supply Specification

SLSN 22D - Supply No. 92221 eyewash shower, desk holder, flexi hose (1500 mm)

SLSN 22V



Supply Specification

SLSN 22V - Supply No. 92225 eyewash shower, plastic wall holder, flexi hose (1500 mm)

Characteristics



- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with two spray heads, upward water stream, with plastic wall holder
- wall mounted, water inlet from the second side of the wall

Technical Specification

Rate of flow	14 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C