Stainless Steel Cleaner's Sink SLVN 02E






Characteristics

- economical aerator, rate of fl ow 6 l/min
- hygienic flush
- suitable for medical facilities
- SLVN 02E stainless steel floor standing combined cleaner's sink with washbasin, grating and automatic tap SLU 08LND (swivel faucet, START/STOP program)
- SLVN 02EB stainless steel floor standing combined cleaner's sink with washbasin, grating and automatic tap SLU 08LNDB (swivel faucet, START/STOP program)
- material stainless steel AISI 304 (1.4301)
- brushed finish

Dimensions



Supply Specification

SLVN 02E - Supply No. 98021 SLVN 02EB - Supply No. 98022 stainless steel cleaner's sink with washbasin, grating, siphon, SLU 08LND (SLVN 02E), SLU 08LNDB and 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLVN 02EB)

Recommended Accessories

Technical Specification

Dimensions Weight	1196 x 690 x 500 mm
• SLVN 02E	22,5 kg
 SLVN 02EB 	22,44 kg
Thickness of material	
∎ sink	1 mm
 apron 	0,8 mm
Operating voltage	
 SLVN 02E 	24 V DC
 SLVN 02EB 	6 V
Power input	
 operating by 24 V DC 	14 W
operating by 6 V	11 W
Battery life	
4 pcs. AA alkaline batteries	approx. 2 years
AA, 1,5 V, 2700 mAh	(100 uses per day)
Rate of flow	12 l/min. (inf. data)
Water inlet	male thread G 1/2"
Water temperature regulation	integrated mixer

Stainless Steel Cleaner's Sinks