

Ceramic Urinal with the Radar Flushing Unit SLP 27S, SLP 27Z, SLP 27B





Installation Drawing



- 1 water outlet Ø 50 mm
- 2 holes for fitting
- 3 water supply
- 4 power supply 24 V DC or 230 V AC

Characteristics

- includes Bluetooth control
- (paid Sanela Control app available for download) • economy flushing by 1 liter of water
- easy installation
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or by remote control SLD 04 without the necessity to dismantle the urinal from the wall (acoustic setting indication)
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing
- monitoring of battery capacity (for models with index B)

Technical Specification

Operating voltage

SLP 27S
SLP 27Z
SLP 27B
Power input
operating by 24 V DC
operating by 6 V
Recommended flow pressure
Rate of flow
Water inlet
Water outlet

24 V DC 230 V AC/50 Hz 6 V

8 W 3 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing



Supply Specification

Α

475

В

225

С

240

* for the height of the front edge of the urinal 650 mm above the floor

D

35

Ε

70

F

360

G

80

Dimensions (mm)

SLP 27 - Chic

SLP 27S

SLP 27Z

SLP 27B

obj. č. 01271 ceramic urinal with the radar flushing unit including Bluetooth module,
 obj. č. 01272 electromagnetic valve, connecting hoses, angle valve with filter and check valve,
 obj. č. 01273 inlet fitting with a rubber seal, siphon, paper drill template, power supply (SLP 27Z)

Recommended Accessories

SLZ 01Y - Supply No. 0 SLZ 01Z - Supply No. 0 SLZ 04Y - Supply No. 0 SLZ 04Z - Supply No. 0 SLZ 04Z - Supply No. 0 SLZ 04X - Supply No. 0 SLZ 06 - Supply No. 0 SLD 04 - Supply No. 0 SLA 11 - Supply No. 0 SLA 11A - Supply No. 0 SLA 11B - Supply No. 0 SLA 11C - Supply No. 0 SANELA CONTROL APP -	 5011 power supply 24 V DC for operating of max. 9 pcs. of flushing units 5042 power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units 5041 power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units 5049 power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units 5060 power supply 24 V DC for operating of max. 1 pc. of flushing unit 5060 power supply 24 V DC for operating of max. 1 pc. of flushing unit 5060 remote control for an adjustment of parameters 6110 deodorising urinal screen - orange colour, mango scent 6111 deodorising urinal screen - red colour, kiwi and grapefruit scent 6112 deodorising urinal screen - transparent colour, honeysuckle scent 6113 deodorising urinal screen - blue colour, cotton bloom scent
---	--