

Sanitary cubicles and partitions for dry areas

SLKA 01W25A



Illustrative photo

Characteristics

- designed for dry areas
- for separating individual WC cubicles
- custom production
- walls made of chipboard, 25 mm thick
- AISI 304 stainless steel fittings
- anodized aluminum profiles
- hygienically safe surface

Technical Specification

Dimensions	total height 2020 mm, cubicle width according to customer specification, gap height from floor 150 mm
Wall filling	chipboard 25 mm thick, standard color grey or white, other colors at extra charge
Doors	chipboard 25 mm thick, color standard grey or white, other colors available for an extra charge self-closing hinges, stainless steel door closer with free/occupied indicator or handle with cylinder lock
Fittings	stainless steel AISI 304
Construction	top profile and U profile for panel mounting to wall, anodized aluminum

Supply Specification

SLKA 01W25A (order number) - Supply No. 40013 set of parts for assembly according to order

Components



U profile for panel
mounting to wall
(anodized aluminum)



top profile
(anodized aluminum)




adjustable foot
(stainless steel)



door handle for cubicle
(stainless steel)



handle with cylinder lock
(stainless steel)



door closer
with free/occupied
indicator or handle



self-closing hinges
(stainless steel)



hook
(stainless steel)



door stop
(stainless steel)