

Safety Eyewash Showers SLSN 21, SLSN 21D, SLSN 21V



SLSN 21

Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, head at an angle of 45 degrees with plastic wall holder
- wall mounted

Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C

Supply Specification

SLSN 21 - Supply No. 92210 eyewash shower, plastic wall holder, flexi hose (1500 mm)



SLSN 21D

Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, head at an angle of 45 degrees with desk holder
- mounting on the desk

Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C

Supply Specification

SLSN 21D - Supply No. 92211 eyewash shower, desk holder, flexi hose (1500 mm)



SLSN 21V

Supply Specification

SLSN 21V - Supply No. 92215 eyewash shower, plastic wall holder, flexi hose (1500 mm)

Characteristics



- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, upward water stream, with plastic wall holder
- wall mounted, water inlet from the second side of the wall

Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,1 MPa
Maximum dynamic pressure	1 MPa
Teplotní rozsah	5 - 80 °C