



Characteristics








- includes Bluetooth control (paid Sanela Control app available for download)
- economical aerator, rate of flow 6 l/min
- hygienic flush
- lead free
- automatic wall-mounted tap behind mirror with electronics
 ALS
- mounting behind mirror
- is destined for cold or premixed water
- water if flowing as long as hands are in the active range under the mirror
- water stops flowing after removal of hands from the active range sensor after adjustable time delay (can be set in range 0,25 - 7,75 s)
- function of automatic water stop after 5 minut of continuous flow
- START/STOP program

Rate of flow

Water inlet

 parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 03

Dimensions



Technical Specification

Dimensions170 x 200 x 300 mmOperating voltage24 V DCPower input7 WActive rangestandard0,13 - 0,19 m■ START/STOP program0,05 - 0,15 mRecommended flow pressure0,1 - 0,6 MPa

6 l/min. (inf. data) male thread G 1/2"

Supply Specification

SLZN 84D - Supply No. 85841 stainless steel mounting holder with spout and electronics, electromagnetic valve, connecting hoses, angle valve with filter

Recommended Accessories

SLZ 01Y Supply No. 05012 power supply 24 V DC for operatin of max. 5 pcs. of taps **SLZ 01Z Supply No. 05011** power supply 24 V DC for operatin of max. 9 pcs. of taps **SLZ 04Y Supply No. 05042** power supply 24 V DC for DIN rail, for operatin of max. 5 pcs. of taps **SLZ 04Z Supply No. 05041** power supply 24 V DC for DIN rail, for operatin of max. 9 pcs. of taps SLZ 04X **Supply No. 10049** power supply 24 V DC for DIN rail, for operatin of max. 15 pcs. of taps - Supply No. 05060 **SLZ 06** power supply 24 V DC pro max. 1 pc. of tap **SLD 03** - Supply No. 07030 remote control for an adjustment of parameters

SANELA CONTROL APP paid Sanela Control app available for download on the App Store and Google Play