

Piezo Shower Control SLS 02P, SLS 02PT



SLS 02P




SLS 02PT

Characteristics



- **hygienic flush**
- **vandal-proof**
- SLS 02P, SLS 02PB are destined for cold and hot water, temperature is regulated by mixer
- SLS 02PT, SLS 02PTB are destined for cold and hot water, temperature is regulated by thermostatic mixer
- safety fuse against scalding
- water flows after soft push of the piezo button
- water stops flowing after adjustable flowing time (can be set in 10 s - 310 s), standard 120 s
- water could be stopped by follow-up soft push of piezo button
- monitoring of battery capacity (for models with index B)
- parameter adjustment using by the remote control SLD 04

Installation Drawing



Technical Specification

Stainless steel cover dimension	170 x 170 x 10 mm
Mounting box dimension	150 x 160 x 65 mm
Operating voltage	
▪ SLS 02P, SLS 02PT	24 V DC
▪ SLS 02PB, SLS 02PTB	6 V
Power input	
▪ operating by 24 V DC	7 W
▪ operating by 6 V	3 W
Battery life	
▪ 4 pcs. AA alkaline batteries AA, 1,5 V, 2700 mAh	approx. 2 years (100 uses per day)
Recommended flow pressure	0,1 - 0,6 MPa
Rate of flow	12 l/min. (inf. data)
Water inlet	male thread G 3/4"
Water outlet	male thread G 3/4"

Supply Specification

SLS 02P - Supply No. 12022	stainless steel cover with electronics, stainless steel mounting box with brass screw coupling, electromagnetic valve, ball valve and mixer, 4 pcs. AA alkaline batteries 1,5 V 2700 mAh (SLS 02PB)
SLS 02PT - Supply No. 12024	stainless steel cover with electronics, stainless steel mounting box with brass screw coupling, electromagnetic valve, ball valve and thermostatic mixer, 4 pcs. AA alkaline batteries 1,5 V 2700 mAh (SLS 02PTB)
SLS 02PB - Supply No. 12023	
SLS 02PTB - Supply No. 12025	

Recommended Accessories

SLZ 01Y - Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of showers
SLZ 01Z - Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of showers
SLZ 04Y - Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers
SLZ 04Z - Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of showers
SLZ 04X - Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers
SLZ 06 - Supply No. 05060	power supply 24 V DC for operating of max. 1 pcs. of showers
SLD 04 - Supply No. 07040	remote control for an adjustment of parameters
SLA 03 - Supply No. 06030	vandal-proof shower head with possibility to set an angle of water flow
SLA 13 - Supply No. 06130	vandal-proof shower head with possibility to set an angle of water flow
SLA 14 - Supply No. 06140	vandal-proof shower head
SLA 28 - Supply No. 06280	shower head
SLA 39 - Supply No. 06390	vandal-proof shower head
SLA 40 - Supply No. 06400	vandal-proof shower head with possibility to set an angle of water flow
SLA 36 - Supply No. 06360	set of 4 pcs. alkaline batteries AA, 1,5 V, 2700 mAh (for models with index B)