Piezo Shower Control SLS 02P



NÀ



SLS 02P

Installation Drawing



Characteristics

- hygienic flush
- vandal-proof
- is destined for cold and hot water, temperature is regulated by mixer
- water flows after soft push of the piezo button
- water stops flowing after adjustable flowing time (can be set in 10 s - 310 s), standard 120 s
- water could be stopped by follow-up soft push of piezo button
- monitoring of battery capacity (for models with index B)
- parameter adjustment using by the remote control SLD 04

Technical Specification

Stainless steel cover dimension Mounting box dimension Operating voltage	170 x 170 x 10 mm 150 x 160 x 65 mm
1 5 5	24 V DC
 SLS 02P 	2
SLS 02PB	6 V
Power input	
operating by 24 V DC	7 W
operating by 6 V	3 W
Battery life	
4 pcs. AA alkaline batteries	approx. 2 years
AA, 1,5 V, 2700 mAh	(100 uses per day)
Recommended flow pressure	0,1 - 0,6 MPa
Rate of flow	12 l/min. (inf. data)
Water inlet	male thread G 3/4"
Water outlet	male thread G 3/4"

Supply Specification

SLS 02P - Supply No. 12022 SLS 02PB - Supply No. 12023 stainless steel cover with electronics, stainelss steel mounting box with brass screw coupling, electromagnetic valve, ball valve and mixer, 4 pcs. AA alkaline batteries 1,5 V 2700 mAh (SLS 02PB)

Recommended Accessories

SLZ 01Y SLZ 04Y SLZ 04Y SLZ 04Z SLZ 04X SLZ 06 SLD 04 SLA 03 SLA 13 SLA 14 SLA 28 SLA 39 SLA 40 SLA 36		Supply No. 05012 Supply No. 05011 Supply No. 05042 Supply No. 05041 Supply No. 05060 Supply No. 05060 Supply No. 07040 Supply No. 06030 Supply No. 06130 Supply No. 06140 Supply No. 06390 Supply No. 06360	power supply 24 V DC for operating of max. 5 pcs. of showers power supply 24 V DC for operating of max. 9 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers power supply 24 V DC for operating of max. 1 pcs. of showers remote control for an adjustment of parameters vandal-proof shower head with possibility to set an angle of water flow vandal-proof shower head shower head vandal-proof shower head vandal-proof shower head vandal-proof shower head vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head vandal-proof shower head vandal-proof shower head vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow vandal-proof shower head by possibility to set an angle of water flow set of 4 pcs. alkaling batteries AA 1 5 V 2700 mAb (for models with index B)
SLA 28	-	Supply No. 06280	shower head
SLA 39		Supply No. 06390	vandal-proof shower head

Piezo Shower Controls