



SLSN 21

### Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, head at an angle of 45 degrees with plastic wall holder
- wall mounted

### Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,15 MPa
Maximum dynamic pressure	0,5 MPa

### Supply Specification

SLSN 21 - Supply No. 92210      eyewash shower, plastic wall holder, flexi hose (1500 mm)



SLSN 21D

### Characteristics

- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, head at an angle of 45 degrees with desk holder
- mounting on the desk

### Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,15 MPa
Maximum dynamic pressure	0,5 MPa

### Supply Specification

SLSN 21D - Supply No. 92211      eyewash shower, desk holder, flexi hose (1500 mm)

SLSN 21V



## Characteristics



- suitable for medical facilities and industry
- used as first aid if eyes impacted by accidents caused by fire, chemical or other dangerous substances
- hand-held eyewash shower with one spray head, upward water stream, with plastic wall holder
- wall mounted, water inlet from the second side of the wall

## Technical Specification

Rate of flow	7 l/min. (inf. data)
Water inlet	1/2" flexi hose
Minimum dynamic pressure	0,15 MPa
Maximum dynamic pressure	0,5 MPa

## Supply Specification

SLSN 21V - Supply No. 92215      eyewash shower, plastic wall holder, flexi hose (1500 mm)