Automatic Toilet Flushing Units for SLR 21 SLW 02A, SLW 02F






SLW 02A



Dimensions



Characteristics

- SLW 02A flushing unit destined for SLR 21, white plastic
- SLW 02F flushing unit destined for SLR 21, black plastic
- system reacts to the user attendance in active range of the sensor at a maximum distance of 0,7 m, minimum stay time in active range is 7,5 s
- water flows after the user leaves active range
- flushing times:
- **"short flushing" (2 s)** = min. stay time in active range is 7,5 s, max. stay time is 45 s **"long flushing" (5 s)**
- = min. stay time in active range is 45 s
- possibility of additional manual flush by push-button (f.e. during the cleaning)
- automatic hygiene flush after each 8 use of toilet and after 24 hours non-use
- parameters adjustment by remote control SLD 03

Technical Specification

Flush plate dimension Operating voltage Power input Active range 220 x 150 mm 24 V DC 13 W 0,6 - 0,75 m

Supply Specification

SLW 02A - Supply No. 04026 SLW 02F - Supply No. 04027 flush plate (white plastic) with electronics, control mechanism with servomotor flush plate (black plastic) with electronics, control mechanism with servomotor

Recommended Accessories

SLZ 01Y	-	Supply No. 05012
SLZ 01Z	-	Supply No. 05011
SLZ 04Y	-	Supply No. 05042
SLZ 04Z	-	Supply No. 05041
SLZ 04X	-	Supply No. 10049
SLD 03	-	Supply No. 07030
SLR 21	-	Supply No. 08210

power supply 24 V DC for operating of max. 2 pcs. of flushing units power supply 24 V DC for operating of max. 4 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 2 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 4 pcs. of flushing units power supply 24 V DC on DIN rail, for operating of max. 7 pcs. of flushing units remote control for an adjustment of parameters mounting frame with concealed tank for wall hung toilets, for installation to the plasterboard and brick wall