Coin and Token Shower Timers for Four to Twelve Showers SLZA 02M, SLZA 02MZ





SLZA 02M




SLZA 02MZ

Characteristics




- hygienic flush
- vandal-proof
- choice of shower by the machine
- after inserting a coin or a token the machine assigns the shower to the user and shows the number of shower on display
- direct control
- after inserting a coin or a token the machine starts water flow on several seconds to indicate the chosen shower
- after set delay the machine starts water flow for paid time
- 30 s before the end of water supply the user is warned by interrupting of water flow
- index Z recessed
- parameters adjustment using by the remote control SLD 05 (adjustment of shower time according to the thrown coin or token, time delay of switch on, possible activation of hygienic flush, time value, current euro exchange, token value, display contrast, possibility switch off some from showers)
- marking of the buttons by symbols could be made to order
- the possibility of obtaining the statistical information, device diagnostics
- lockable
- material AISI 304
- could be made to order from stainless steel AISI 316L
- brushed finish


Installation Drawing



132

SLZA 02M





132

SLZA 02MZ

Technical Specification

Dimension of hole in the wall for models with index Z Operating voltage Power input

Types of coins

Time delay of switch on Delay time for paid 5 CZK

335 x 200 x 125 mm

24 V DC 91 W

(depends on the accessories and the number of showers)

5, 10, 20 and 50 CZK, 1 and 2 EUR, metal token 0 - 255 s, standard 30 s

0 - 255 s, standard 30 s

SLZA 02MZ - Supply No. 88022 stainless steel coin machine with electronics, coin holder and coin box,

set of keys (2 pcs.), mounting frame

Necessary Accessories



SLZA 15 88150 Valves distributor on DIN rail
--




SLZA 20 88200	Shower control without piezo button - premixed water
---------------	--



SLZA 20H 88205	Shower control without piezo button - for cold and hot water, temperature regulated by mixer
----------------	--



SLZA 20T 88206 - for cold and hot water, temperature regulated by thermostatic mixer
--



SLZA 21 88	210	Stainless steel shower panel without piezo button - premixed water
------------	-----	--



SLZA 21H 88215	Stainless steel shower panel without piezo button - for cold and hot water, temperature regulated by mixer
----------------	--



SLZA 21T

88216

Stainless steel shower panel without piezo button - for cold and hot water, temperature regulated by thermostatic mixer

Recommended Accessories

SLZA 50 SLZ 01Y	-	Supply No. 88500 Supply No. 05012	set of 50 pcs. of tokens for coin machine power supply 24 V DC for operating of max. 5 pcs. of showers
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of showers
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of showers
SLZ 04X		Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers
SLD 05		Supply No. 07050	remote control for an adjustment of parameters
SLA 03	-	Supply No. 06030	vandal-proof shower head
SLA 39	-	Supply No. 06390	vandal-proof shower head
SLA 40	-	Supply No. 06400	vandal-proof shower head with possibility to set an angle of water flow