

## Stainless steel wall mounted shower panel without piezo button, with flowmeter



SLZA 21K



SLZA 21KH, SLZA 21KT

### Supply Specification:

- SLZA 21K – supply No. 89211 stainless steel wall mounted
- SLZA 21KH – supply No. 89212 shower panel with fitting and
- SLZA 21KT – supply No. 89213 electromagnetic valve, ball, valve and brass fitting and flowmeter

### Characteristics:

- only for use with set of SLZA 02M
- mounting on the tiles, suitable for renovation
- SLZA 21K - destined for premixed water
- SLZA 21KH - destined for hot and cold water, temperature regulation by mixer
- SLZA 21KT - destined for hot and cold water, temperature regulation by thermostatic mixer
- after payment into coin shower timer and adjusted time delay water starts to flow from shower head
- shower time can not be interrupted
- including the measurement of water flow, necessary to use SLZA 16
- material stainless steel AISI 304, brushed, material stainless steel AISI 316L could be made to order


### Technical Specification:

Operating voltage	24V DC
Power input	6,5 W

## Stainless steel wall mounted shower panel with piezo button and with flowmeter



SLZA 21PK



SLZA 21PKH, SLZA 21PKT

### Supply Specification:

- SLZA 21PK – supply No. 88214 stainless steel wall mounted
- SLZA 21PKH – supply No. 89215 shower panel with piezo button,
- SLZA 21PKT – supply No. 89216 and fitting and electromagnetic valve, ball valve and brass fitting and flowmeter

### Characteristics:

- only for use with set of SLZA 02N
- mounting on the tiles, suitable for renovation
- SLZA 21PK - destined for premixed water
- SLZA 21PKH - destined for hot and cold water, temperature regulation by mixer
- SLZA 21PKT - destined for hot and cold water, temperature regulation by thermostatic mixer
- push piezo button to start water flowing
- with piezo button it is possible start and stop water in pre-paid time
- including the measurement of water flow, necessary to use SLZA 16
- material stainless steel AISI 304, brushed, material stainless steel AISI 316L could be made to order

### Technical Specification:

Operating voltage	24V DC
Power input	6,5 W